

VIEW OF DISCHARGE

INLET & DISCHARGE FLANGES TO MATE FLUSH & SQUARE WITH FLAT FACE FLANGE ONLY. USE FULL FACE GASKETS.

V-BELT DRIVEN UNITS: MOTOR TO BE LOCATED ON INLET SIDE OF HORIZONTAL FLOW UNITS & ON DRIVE SHAFT SIDE OF VERTICAL FLOW UNITS.

AD - MAXIMUM SHEAVE WIDTH (SEE OVERHUNG LOAD LIMIT K-24102)

AE - MINIMUM SHEAVE DIAMETER (SEE OVERHUNG LOAD LIMIT K-24102)

ALL DIMENSIONS IN MM, IMPERIAL DIMENSIONAL #90775021

DISCH. LOCATION	DRIVE LOCATION	
	LH	RH
TOP	CW	CCW
BOTTOM	CCW	CW

UNIT IS BUILT TO CUSTOMERS SPECIFIED ORIENTATION


MODEL	C	M	N	U MM	V MM	KEYWAY MM	INLET AA	DISCH AA'	AB	AD	AE	AF	AG	AH	AJ	AK	JAK	APPROX WEIGHT
800	1193	475	125	70.0	102.0	20.0X8.0	254	254	352	183	335	704	508	216	356	660	356	909 KG
1000	1346	551	"	"	"	20.0X8.0	"	"	"	"	"	"	635	"	"	813	813	1136 KG

MODEL	X1	X2	X3	X4	Y1	Y2	W	Z
800	99	199	-	298	49	146	M16x2	18
1000	93	187	281	375	49	146	M16x2	22

CERTIFIED CORRECT FOR
 CUSTOMER ORDER No. _____
 ROOTS ORDER No. _____
 DATE _____

REVISIONS	BY	CHANGE NOTICE	CHKD.	APP.	V-BELT DRIVE DATA
					BELTS
					DRIVE SHEAVE
					DRIVEN SHEAVE
					CENTER DISTANCE

RAM X™
TRI-LOBE BLOWERS
 METRIC
 MODELS 800 & 1000



Dresser ROOTS, Dresser, Inc.
 Connersville, IN USA

DR	CHKD	APP	90776021	REV.
----	------	-----	----------	------