



	VALVE SIZE	"A"	"B"	"C"
	1	3.5	1.315	1.625
	1.25	3.5	1.660	2
	1.5	4	1.900	2.25
	2	4	2.375	2.75
	2.5	5	2.875	3.25
	3	5.5	3.5	3.875
	4	6	4.5	4.875
	5	7	5.5625	6.125
	6	8	6.625	7.125

SEALING MEMBER MATERIALS		
	MATERIAL	TEMPERATURE RANGE
	Buna-N	-60 to 225°F
	Neoprene	-40 to 225°F
	Butyl	-65 to 325°F
	Hypalon	-20 to 300°F
X	EPDM	-40 to 350°F
	Viton	-20 to 400°F
	Teflon	-20 to 450°F
	Silicone	-100 to 500°F
	FDA Approved White Neoprene	-40 to 225°F

	STYLE	BODY	INTERNALS	PSI C.W.P.
	5002-AL	Aluminum	Aluminum	50
	5002-BR	Brass	Brass	150
	5002-304	304 Stainless Steel	304 Stainless Steel	150
	5002-316	316 Stainless Steel	316 Stainless Steel	150
X	5002-CLASS A	Steel	Aluminum	150
	5002-CLASS D	Steel	Cadmium Plate Steel	150