



INLET/DISCH FLANGES

MODEL	X1	X2	X3	X4	Y1	Y2	W	Z
600	86.9	173.7	--	260.6	42.4	127	M16X2	18
770	82.6	165	247.7	330	42.4	127	M16X2	22

INLET & DISCHARGE FLANGES TO MATE FLUSH & SQUARE WITH FLAT FACE FLANGE ONLY. USE FULL FACE GASKETS.

FOR V-BELT DRIVEN UNITS MOTOR TO BE LOCATED ON DRIVE SHAFT SIDE OF BLOWER

ALTERNATE POSITIONS #2, #3 & #4 ALSO AVAILABLE

AD-SHEAVE WIDTH
AE-SHEAVE DIAMETER

ALL DIMENSIONS IN MILLIMETERS

(SEE 90762021 FOR IMPERIAL DIMENSIONS)

MODEL	A	B	C	D	E	F	G	H	J	K	M	N	O	P	U MM	V MM	KEYWAY MM	AG	AH	AJ	AK	AA	AB	AD	AE	APPROX WEIGHT
600	660.4	731.3	1046	254	273	337	12.7	25.4	114.3	76	410	115.8	464	591	60.00	76.20	18X7	445	93.4	311	578	219	295	112	300	600KG
770	660.4	877.3	1192	254	273	410	12.7	25.4	114.3	76	483	115.8	464	591	60.00	76.20	18X7	572	93.4	311	724	219	295	112	300	700KG

CERTIFIED CORRECT FOR
 CUSTOMER ORDER No. _____
 ROOTS ORDER No. _____
 DATE _____

REVISIONS	BY	CHANGE NOTICE	CHKD.	APP.

RAM X™ TRILOBE BLOWERS
 MODEL 600 & 770



Dresser ROOTS, Dresser, Inc.
 Connersville, IN USA

DR	CHKD	APP	90768022	REV.
----	------	-----	----------	------