



INLET AND DISCHARGE FLANGES TO MATE FLUSH AND SQUARE WITH FLAT FACE FLANGES ONLY. USE FULL FACE GASKETS

FOR V-BELT DRIVEN UNITS MOTOR TO BE LOCATED ON INLET SIDE OF BLOWER

	12"FLG
OPENING	12.00
BOLT CIRCLE	17.00
FLANGE O.D.	19.00
No TAPPED HOLES	12
SIZE HOLES	7/8-9
TAP DEPTH	1.31

W - INLET & DISCHARGE
 AD - SHEAVE WIDTH
 AE - SHEAVE DIAMETER
 AW - JET INLET

700 DVJ DRY VACUUM WHISPAIR BLOWER

ALL DIMENSIONS IN INCHES

FRAME SIZE	A	B	C	D	E	F	G	H	J	K	M	N	O	P	R	U	V	KEYWAY	W	AA	AA'	AD	AE	AW	AX	APPROX. WEIGHT
721	19.00	27.00	39.38	17.00	7.25	12.38	.50	1.00	4.50	3.00	15.25	4.56	24.88	24.25	13.50	2.375	3.00	.625 x .313	12"FLG	9.00	15.25	4.43	11.80	12"FLG	5.50	1750

CERTIFIED CORRECT FOR
 CUSTOMER ORDER No. _____
 ROOTS ORDER No. _____
 DATE _____

V-BELT DRIVE DATA	
BELTS	C-CHGD LIFTING LUGS NEP 10/19/95 1/4 399V
DRIVE SHEAVE	B-REVISED APPROX. WEIGHT JHB 10-21-93
DRIVEN SHEAVE	A-CORRECTED BREATHER RVE 2/24/93
CENTER DISTANCE	REVISIONS

ROOTS DRESSER		DRESSER INDUSTRIES, INC ROOTS DIVISION 900 WEST MOUNT STREET CONNERSVILLE, INDIANA 47331	
JHB DR 10-21-92	CHKO DB	DLB APP 1/9/93	873-962-021