

# pdbl<sup>o</sup>wers Premium Blower Grease

## Synthetic EP Aluminum Complex Grease NLGI #2

Our premium synthetic grease is ideal for blowers that utilize grease lubrication of the drive-end bearings. Special additives give it water wash off properties that far exceed other greases, providing exceptional performance in the most demanding applications.

pdbl<sup>o</sup>wers synthetic aluminum complex grease is also available in a food grade formulation.



### TYPICAL PROPERTIES

NLGI Grade	2
Penetration, 60 Strokes	295
Dropping Point	500°F (260°C)
Water Washout, Loss @ 100°F (37.8°C)	5% max
Four Ball EP (Weld) Kg	415
Load Wear Index Kg	40
Four Ball Wear, Scar mm	0.60
Rust Test (ASTM D665)	PASS
Temperature Range	5°F to 300°F (-15°C to 149°C)
Part Number	50467

### PERFORMANCE ADVANTAGES

- Exceptional thermal & oxidative stability
- Excellent resistance against water contamination
- Outstanding materials compatibility
- Superior rust and corrosion control
- Reduced maintenance costs and downtime
- Non-toxic / Non-hazardous

### MAINTENANCE TIPS



- Do not overgrease
- Apply with a hand pump only, as a pneumatic grease gun can fill too quickly and damage the seals
- Keep grease vents clear to allow grease to escape and prevent damage to seals
- Reference blower manual for recommended greasing intervals based on your blower's operating hours
- If you are switching from another type of grease, make sure to fully purge the old grease as the two greases may separate if mixed