Roots 33 URAI Blower

Comparison with Sutorbilt Legend 3M



Both the 33 URAI and 3M Legend utilize oil lubrication on the gear end and grease on the drive end.

	36 URAI	3M LEGEND
Required Oil (Horizontal Unit)	16 oz	18 oz
Required Oil (Vertical Unit)	8.5 oz	9 oz
Grease Type	Aluminum Complex NLGI #2	Lithium Complex NLGI #2

Gear End Oil Lubrication

Blowers ship dry from factory and oil must be added before startup. Oil must be an industrial type non-detergent, rust inhibiting, anti-foaming oil of the correct viscosity. See your manual or contact us for assistance selecting the viscosity.

Drive End Grease Lubrication

These manufacturers use different types of grease which should not be mixed. If you plan to change to a different grease than the type that came in your blower, a full purge must be done.

SPECIFICATIONS	ROOTS 33 URAI	SUTORBILT 3M LEGEND
Flow Range:	to 195 CFM	to 186 CFM
Max Δ Pressure:	12 psi	12 psi
Max Δ Vacuum:	15" Hg	15" Hg
Maximum RPM:	3600	3600
Minimum RPM:	1090	1091
Max ΔT:	225°F	180°F
Connection:	2" FPT	2" FPT
Shaft Diameter:	3/4"	3/4"
Unit Weight:	74 lb	110 lb

CONFIGURATIONS

Both models feature movable mounting feet that allow the blower to be flipped into four different configurations. The manufacturer's part numbers are listed below.









	LEFT HAND	TOP DRIVE	RIGHT DRIVE	BOTTOM DRIVE
33	6510502L	6510502T	6510502R	6510502B
ЗМ	GABMC*A	GABMA*A	GABMD*A	GABMB*A

*The sixth character in the Sutorbilt part number indicates the series designation. As of this print, the current series is S. Previous series include R, P and L.

Roots 33 URAI Blower


Dimensional Comparison with Sutorbilt 3M

While these models are typically considered drop-in equivalents, there are minor differences which should be considered for your situation.

SHAFT AND CONNECTIONS


Shaft size (U) and connection size (C) are the most important dimensions to compare. With these two models both measurements are the same.


To determine whether any changes to your piping or enclosure will be needed, take note of the placement of the connections (X,H) and the shaft (P,W).





MOUNTING FEET


The placement of the bolt slots in the mounting feet is also important to consider. Both units feature universal mounting feet that can be moved to accommodate changes in configuration.












MAKE	MODEL	A	В	С	D	E	G	н	J	К	L	М	N	P1	P2	Q	R	S	Т	U	w	Х	Y
Roots	33 URAI	12.13	12.13	2" NPT	7.25	2.5 - 2.88	3.5	8.88	4.13	7.63	3 - 3.25	6.25	2.44	5	5	3.88	12.81	7.75	0.25	0.75	8.5	6.75	0.44 bolts
Sutorbilt	3M	11.26	12.92	2" NPT	7.75	2.68	3.5	8.88	4.38	7.62	3.13	6.3	2.05	5	4.5	3.88	11.88	7.76	0.25	0.75	8	6.25	0.62 x 1.12

All measurements shown in inches

© pdblowers, Inc. 1-800-536-9933 | www.pdblowers.com


Roots 33 URAI

PRESSURE PERFORMANCE



Sutorbilt 3M

PRESSURE PERFORMANCE



Roots 33 URAI

VACUUM PERFORMANCE

Sutorbilt 3M

VACUUM PERFORMANCE

